



Social Distancing Maintenance Through Proximity Sensors

Rakesh Mohapatra^{1,*}, Rita de Fátima Muniz² , Wagner Bandeira Andriola² 

¹Computer Science and Engineering, OEC Engineering College, OD, India; rakeshmohapatra@gmail.com.

²Federal University of Ceará, Fortaleza, CE, Brazil; ritamunizjijoca@gmail.com; w_andriola@yahoo.com.

Citation:



Mohapatra, R., Muniz, R., Andriola, W.B. (2021). Social distancing maintenance through proximity sensors. *Big data and computing visions*, 1 (4), 200-205.

Received: 04/07/2021

Reviewed: 23/08/2021

Revised: 13/09/2021


Accept: 10/10/2021

Abstract

The term Social-Distancing (S-D) is a way to stop or slow the spreading of contagious disease. In other words, it means less physical communication between two or more persons. In S-D the gap between two living beings (normally human) is 6 feet (two meters). In this short note, we propose a proximity-based alarming device that alerts the user when he or she crosses the threshold S-D limit. This equipment will help people to maintain safe distance among themselves that ultimately help avoidance of spreading coronavirus. This model is the integration of the proximity sensor and an alarming mechanism. This prototype has been tested on a toy for validation purposes.

Keywords: Covid, Proximity, Sensor, Corona, Social distancing, Alarm.

1 | Introduction

 Licensee **Big Data and Computing Vision**. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<http://creativecommons.org/licenses/by/4.0>).

All coronavirus disease 2019 (COVID-19), is a contagious disease which is caused by severe acute respiratory syndrome coronavirus 2 (SARS-CoV-2) [1]. In December 2019, the first case of COVID-19 has been detected at Wuhan the capital of China's Hubei province [2] and [3]. Now, this has been spread globally, resulting in the ongoing coronavirus pandemic. As per the report published by the World Health Organization (WHO), the virus mainly spread due to close contact [2]. The small droplets produced through talking, sneezing, and coughing are the carrier of the CORONA virus [4]. This COVID-19 also can be spread through touching the infected surface or objects and by touching the face as well [5] and [6]. As of today (5th -April-2020), more than 1.2 million cases have been reported from all over the world that results in 64,700 deaths and more than 247,000 people have recovered [7] and [8]. The enhancement of science and technology leads to make the life more comfortable than older days. The emerging technologies like software engineering [1] and [2], energy management [3], [4], [5], wireless sensor network [6]- [13], face recognition [14], neural network [15], routing [16] and [17], distributive environment [18], mixed environment [19] bellman algorithm [20], programming language [21], neutrosophic shortest path [22], [23], [24], optimal path [25], multi-objective optimal path [26], transportation problem [27], [28], [29], uncertainty problem [30]- [35], fuzzy shortest path [36] and [37], powershell [38], answer note [39], making the products more



Corresponding Author: rakeshmohapatra@gmail.com



10.22105/BDCV.2021.142229

intelligent and self-healing based. The smart city [40] and [41] applications like smart water [43], [44], smart agriculture [45] smart grid [41] and [42], smart parking [46], smart resource management, etc. are based on IoT [46] and [47] and IoE technologies. In this short-note, we are not going to discuss the medical background of COVID-19 neither we are going to discuss the history of COVID-19. This information is already available in various forums like social networks, journals, YouTube videos, etc. The primary focus of our work is to warn the people when they knowingly or unknowingly cross the threshold of an S-D limit that is 6 feet or 2 meters. The proposed model is the integration of Proximity Sensors (PS) and an alarming model. To design this social Distancing Device (S2D) we have borrowed the concept of the PS in the car.

1.1 | Proximity Sensor

The PS which is also known as the perimeter sensor, is responsible to trigger the alarm when an object is close to the sensor perimeter. The PS can detect the presence of a non-metallic object without having a touch. PS uses semiconductor outputs, which gives a longer service life. PS can be used in temperatures ranging from -40 to 200°C. PS performance is independent of the colors of the object. The basic function of PS is the emitting of electromagnetic radiations (Ex. Infrared (IR)), and observe for a change in the echo signal. There are several types of PS are available based on the PS's target [10]. In-car, the PS uses echo-times from sound waves that bounce off nearby objects. The PS able to calculate the distance between the objects and the car. The same concept we have transferred into a portable pocket device called "S2D" for the human. In this case, if two persons with an S2D device come in close contact that is within two meters range then both the person will get a warning for social distancing. The alarm can be in any forms like a sound or a digital message. *Fig. 1* illustrates the distancing concept with the help of PS. *Fig. 2* illustrates the internal element of inductive PS.




Fig. 1. Deployed proximity sensors with their perimeter.

1.1.1 | Simulation of S2D

In the designing process of S2D, we have used PS and an alarming system. *Fig. 3* illustrates the alarming process when the sensors are touching the perimeter of each other. The replication of the same when we have applied on toy for the alarming about social distancing. This process creates an alarm for each human when they knowingly and unknowingly enter into the close proximity of each other. *Fig. 4* illustrates the PS based human interaction. In *Fig. 4*, two case study has been illustrated in the first case (left side of image) where the two men are maintaining proper social distancing whereas in the right side of the image the two men are crossing the proximity-based threshold limitation hence there is an alarm as a warning message.




Fig. 2. Internal elements of inductive proximity sensors.




Fig. 3. Interaction among PS.

In this short note, we have proposed the idea that the PS of the car can also be used for humans as an alarming device during this crucial condition of COVID-19. As we all know, until today no vaccine has been developed for COVID-19 hence except Social-Distancing S-D there is no other way to stop the spreading of the coronavirus. Through this proposed model the users can get an alarm or warning which helps them to maintain a safe distance in case of emergency interaction.

Steps	Procedure
Step 1	Inputs: Human Interaction
Step 2	Output: Alarm Generation
Step 3	If (S-D > Minimum Threshold Limit)
Step 4	Then
Step 5	No alarm
Step 6	Else
Step 7	Trigger Alarm
Step 8	Repeat: Steps 3-7 For (Each new interaction)




Fig. 4. PS based human interaction.

5 | Conclusion and Future

In this paper, we just tried to help the society to fight against COVID-19. In the absence of a vaccine for COVID-19, Social-Distancing S-D is the only solution left with human beings. Hence, in this short note, we have tried to use the PS of the car for humans. In case of emergency interaction or in any other circumstances when interaction cannot be avoidable by using this S2D device the users can maintain a safe distance from each other. The alarming system of S2D warns the human when they cross the threshold minimum safe distance.

References

- [1] Murphy, G. C. (2010, November). Human-centric software engineering. *Proceedings of the FSE/SDP workshop on Future of software engineering research* (pp. 251-254).
- [2] Mohapatra, H., & Rath, A. K. (2020). *Fundamentals of software engineering: designed to provide an insight into the software engineering concepts*. BPB Publications.
- [3] Mohapatra, H., Debnath, S., & Rath, A. K. (2019). Energy management in wireless sensor network through EB-LEACH. *International journal of research and analytical reviews (IJRAR)*, 56-61.
- [4] Mohapatra, H., Debnath, S., Rath, A. K., Landge, P. B., Gayen, S., & Kumar, R. (2020). An efficient energy saving scheme through sorting technique for wireless sensor network. *International journal*, 8(8), 4278-4286.
- [5] Mohapatra, H., Rath, A. K., Landge, P. B., Bhise, D. H. I. R. A. J., Panda, S., & Gayen, S. A. (2020). A comparative analysis of clustering protocols of wireless sensor network. *International journal of mechanical and production engineering research and development (IJMPERD) ISSN (P)*, 10(3), 8371-8385.

- [6] Mohapatra, H., & Rath, A. K. (2019). Fault tolerance through energy balanced cluster formation (EBCF) in WSN. *Smart innovations in communication and computational sciences* (pp. 313-321). Springer, Singapore. https://doi.org/10.1007/978-981-13-2414-7_29
- [7] Mohapatra, H., & Rath, A. K. (2019). Fault tolerance in WSN through PE-LEACH protocol. *IET wireless sensor systems*, 9(6), 358-365.
- [8] Mohapatra, H., & Rath, A. K. (2021). Fault tolerance in WSN through uniform load distribution function. *International journal of sensors wireless communications and control*, 11(4), 385-394. <https://doi.org/10.2174/2210327910999200525164954>
- [9] Mohapatra, H., & Rath, A. K. (2019). Fault-tolerant mechanism for wireless sensor network. *IET wireless sensor systems*, 10(1), 23-30. DOI: [10.1049/iet-wss.2019.0106](https://doi.org/10.1049/iet-wss.2019.0106)
- [10] Mohapatra, H., & Rath, A. K. (2020). Survey on fault tolerance-based clustering evolution in WSN. *IET networks*, 9(4), 145-155.
- [11] Mohapatra, H., Rath, A. K., Lenka, R. K., Nayak, R. K., & Tripathy, R. (2021). Topological localization approach for efficient energy management of WSN. *Evolutionary intelligence*, 1-11. <https://doi.org/10.1007/s12065-021-00611-z>
- [12] Mohapatra, H., Rath, S., Panda, S., & Kumar, R. (2020). Handling of man-in-the-middle attack in wsn through intrusion detection system. *International journal*, 8(5), 1503-1510.
- [13] Mohapatra, H. (2021). *Designing of fault tolerant models for wireless sensor network* (Ph. D Dissertation, Veer Surendra Sai University of Technology). Retrieved from <http://hdl.handle.net/10603/333160>
- [14] Nirgude, V., Mahapatra, H., & Shivarkar, S. (2017). Face recognition system using principal component analysis & linear discriminant analysis method simultaneously with 3d morphable model and neural network BPNN method. *Global journal of advanced engineering technologies and sciences*, 4(1), 1-6.
- [15] Mohapatra, H. (2009). HCR by using neural network (Master's thesis, M. Tech_s Desertion, Govt. College of Engineering and Technology, Bhubaneswar).
- [16] Mohapatra, H., & Rath, A. K. (2021). A fault tolerant routing scheme for advanced metering infrastructure: an approach towards smart grid. *Cluster computing*, 2193-2211. <https://doi.org/10.1007/s10586-021-03255-x>
- [17] Panda, M., Pradhan, P., Mohapatra, H., & Barpanda, N. K. (2019). Fault tolerant routing in heterogeneous environment. *International journal of scientific & technology research*, 8(8), 1009-1013.
- [18] Ande, V. K., & Mohapatra, H. (2015). SSO mechanism in distributed environment. *International journal of innovations & advancement in computer science IJIACS*, 4(6), 133-136.
- [19] Kumar, R., Jha, S., & Singh, R. (2020). A different approach for solving the shortest path problem under mixed fuzzy environment. *International journal of fuzzy system applications (IJFSA)*, 9(2), 132-161.
- [20] Broumi, S., Dey, A., Talea, M., Bakali, A., Smarandache, F., Nagarajan, D., ... & Kumar, R. (2019). Shortest path problem using Bellman algorithm under neutrosophic environment. *Complex & intelligent systems*, 5(4), 409-416. <https://doi.org/10.1007/s40747-019-0101-8>
- [21] Mohapatra, H. (2018). *C programming: practice cpp*. Kindle EBook.
- [22] Kumar, R., Dey, A., Broumi, S., & Smarandache, F. (2020). A study of neutrosophic shortest path problem. *Neutrosophic graph theory and algorithms* (pp. 148-179). IGI Global. DOI: [10.4018/978-1-7998-1313-2.ch006](https://doi.org/10.4018/978-1-7998-1313-2.ch006)
- [23] Kumar, R., Edalatpanah, S. A., Jha, S., & Singh, R. (2019). A novel approach to solve gaussian valued neutrosophic shortest path problems. *International journal of engineering and advanced technology*, 8(3), 347-353.
- [24] Kumar, R., Edaltpanah, S. A., Jha, S., Broumi, S., & Dey, A. (2018). Neutrosophic shortest path problem, *Neutrosophic sets and systems*, 23, 5-15.
- [25] Kumar, R., Edalatpanah, S. A., & Mohapatra, H. (2020). Note on "optimal path selection approach for fuzzy reliable shortest path problem". *Journal of intelligent & fuzzy systems*, 39(5), 7653-7656. DOI: [10.3233/JIFS-200923](https://doi.org/10.3233/JIFS-200923)
- [26] Kumar, R., Edalatpanah, S. A., Jha, S., Broumi, S., Singh, R., & Dey, A. (2019). A multi objective programming approach to solve integer valued neutrosophic shortest path problems, *Neutrosophic sets and systems*, 24, 134-148.

- [27]Kumar, R., Edalatpanah, S. A., Jha, S., & Singh, R. (2019). A Pythagorean fuzzy approach to the transportation problem. *Complex & intelligent systems*, 5(2), 255-263. <https://doi.org/10.1007/s40747-019-0108-1>
- [28]Pratihari, J., Kumar, R., Dey, A., & Broumi, S. (2020). Transportation problem in neutrosophic environment. *Neutrosophic graph theory and algorithms* (pp. 180-212). IGI Global.
- [29]Pratihari, J., Kumar, R., Edalatpanah, S. A., & Dey, A. (2021). Modified Vogel's approximation method for transportation problem under uncertain environment. *Complex & intelligent systems*, 7(1), 29-40. <https://doi.org/10.1007/s40747-020-00153-4>
- [30]Gayen, S., Jha, S., Singh, M., & Kumar, R. (2019). On a generalized notion of anti-fuzzy subgroup and some characterizations. *International journal of engineering and advanced technology*, 8(3), 385-390.
- [31]Gayen, S., Smarandache, F., Jha, S., & Kumar, R. (2020). Interval-valued neutrosophic subgroup based on interval-valued triple t-norm. *Neutrosophic sets in decision analysis and operations research* (pp. 215-243). IGI Global.
- [32]Gayen, S., Smarandache, F., Jha, S., & Kumar, R. (2020). Introduction to interval-valued neutrosophic subring. *Neutrosophic sets and systems*, 36, 220-245.
- [33]Gayen, S., Smarandache, F., Jha, S., Singh, M. K., Broumi, S., & Kumar, R. (2020). Introduction to plithogenic hypersoft subgroup, *Neutrosophic sets and systems*, 33, 208-233.
- [34]Gayen, S., Smarandache, F., Jha, S., Singh, M. K., Broumi, S., & Kumar, R. (2020). Introduction to plithogenic subgroup. *Neutrosophic graph theory and algorithms* (pp. 213-259). IGI Global. DOI: [10.4018/978-1-7998-1313-2.ch008](https://doi.org/10.4018/978-1-7998-1313-2.ch008)
- [35]Gayen, S., Smarandache, F., Jha, S., Singh, M. K., Broumi, S., & Kumar, R. (2020). Soft subring theory under interval-valued neutrosophic environment, *Neutrosophic sets and systems*, 36, 193-219.
- [36]Kumar, R., Edalatpanah, S. A., Jha, S., Gayen, S., & Singh, R. (2019). Shortest path problems using fuzzy weighted arc length. *International journal of innovative technology and exploring engineering*, 8(6), 724-731.
- [37]Kumar, R., Jha, S., & Singh, R. (2017). Shortest path problem in network with type-2 triangular fuzzy arc length. *Journal of applied research on industrial engineering*, 4(1), 1-7. DOI: [10.22105/jarie.2017.48858](https://doi.org/10.22105/jarie.2017.48858)
- [38]Mohapatra, H., Panda, S., Rath, A., Edalatpanah, S., & Kumar, R. (2020). A tutorial on powershell pipeline and its loopholes. *International journal of emerging trends in engineering research*, 8(4), 975-982.
- [39]Kumar, R., Edalatpanah, S. A., Gayen, S., & Broum, S. (2021). Answer note "a novel method for solving the fully neutrosophic linear programming problems: suggested modifications". *Neutrosophic sets and systems*, 39(1), 148-152.
- [40]Mohapatra, H., Balajee, R. M., Rath, A., & Devi, H. S. (2020). Comparative case study on smart city versus digital city. In *Handbook of research of internet of things and cyber-physical systems an integrative approach to an interconnected future*. Apple Academic Process (AAP).
- [41]Panda, H., Mohapatra, H., & Rath, A. K. (2020). WSN-based water channelization: an approach of smart water. *Smart cities—opportunities and challenges*, 58, 157-166. https://doi.org/10.1007/978-981-15-2545-2_15
- [42]Mohapatra, H., & Rath, A. K. (2020, October). Nub less sensor based smart water tap for preventing water loss at public stand posts. *2020 IEEE microwave theory and techniques in wireless communications (MTTW)*, 1, pp. 145-150. IEEE. DOI: [10.1109/MTTW51045.2020.9244926](https://doi.org/10.1109/MTTW51045.2020.9244926)
- [43]Rout, S. S., Mohapatra, H., Nayak, R. K., Tripathy, R., Bhise, D., Patil, S. P., & Rath, A. K. (2020). Smart water solution for monitoring of water usage based on weather condition. *International journal of emerging trends in engineering research*, 8(9), 5335-5343.
- [44]Mohapatra, H., & Rath, A. K. (2021). IoE based framework for smart agriculture. *Journal of ambient intelligence and humanized computing*, 1-18. <https://doi.org/10.1007/s12652-021-02908-4>
- [45]Mohapatra, H., & Rath, A. K. (2021). An IoT based efficient multi-objective real-time smart parking system. *International journal of sensor networks*, 37(4), 219-232.
- [46]Mohapatra, H., & Rath, A. K. (2019). Detection and avoidance of water loss through municipality taps in India by using smart taps and ICT. *IET wireless sensor systems*, 9(6), 447-457.
- [47]Mohapatra, H. (2020). Offline drone instrumentalized ambulance for emergency situations. *IAES international journal of robotics and automation*, 9(4), 251-255.